Standard Indoor Locker System

Parcel Pending's indoor locker systems are designed and engineered for multiple package management applications that facilitate a seamless and convenient package delivery process for multifamily properties.

Parcel Pending parcel lockers make package management simple, freeing up time and space for both residents and property management.



Locker Specs

- 18-gauge double-reinforced cold-rolled steel construction
- Operational conditions: temperature +41° to +95° F humidity up to 80% non-condensing
- Control towers feature an industrial-grade indoor touchscreen, a camera for photo capture, a keypad, a scanner supporting 1D and 2D barcode reading, and speakers
- Each door features smart package sensors to detect packages and other items
- Locker design is compliant with the Americans with Disabilities Act (ADA) - Every door size is available within the "reachable" range for wheelchair users, and control touchscreen and barcode scanner are also compliant for wheelchair accessibility
- Locker system is anchored on the wall or on the ground depending on setup and location
- Each tower is bolted and secured together
- Cloud-based video surveillance is available as an option
- Lockers are certified for UL/CSA safety standards UL/CSA 62368 and UL/CSA 60950
- Lockers are RoHS and REACH compliant

Colors






Jet Black (RAL9005)

Custom wraps available



Standard Indoor Locker System



Tower specs

Total Doors (internal size in inches W x D x H) / (Max weight in lbs)	D13 control tower	D6 control tower	D18	D12	56	513	M23	D4	D1	OS-3
Small (13.59 x 23.1 x 4.23) / (33)	7	1	12			11				
Medium (13.59 x 23.1 x 9.25) / (33)	4	2	4	10	5	2				
Large (13.59 x 23.1 x 24.33) / (44)	2	1	2	2	1					
X-Large (13.59 x 23.1 x 36.85) / (44)		2						4		
H-Small (7.39 x 23.1 x 4.23) / (33)							17			
H-Medium (7.39 x 23.1 x 9.25) / (33)							6			
Ultra (30.42 × 22.06 × 74.33) / (220)									1	
OS-3 (44.9 × 22.4 × 24) / (220)										3
Weight (lbs)	397	353	408	375	203	294	388	309	287	419

Tower measurements (in inches W x D x H)*

D13, D6, D18, D12, D4, D1	39.5 x 24 x 80.9~81.7
S6	22.5 x 24 x 80.9~81.7
S13	22.5 x 24 x 79.7~80.5
M23	27 x 24 x 79.7~80.5
OS-3	53.7 x 24 x 79.7~80.5

^{*} includes slight adjustments to tower feet for balancing and leveling purposes